10. Lewis uses a smart watch to track the distance he walks each day for a week. His target is to walk 5 kilometres or more each day.

The program will find the highest the number of consecutive days Lewis meets this target.

For example, if the data was 5.2, 4.2, 4.0, 4.8, 5.8, 5.2, 6.4

The expected output should be 3.

•••

The following code has been developed to find the highest number of consecutive days Lewis has met his target but there is an error.

```
Line 09
        FUNCTION consecutiveDays (ARRAY OF REAL values)
        RETURNS INTEGER
Line 10
          DECLARE counter INITIALLY 0
Line 11
          DECLARE longestStreak INITIALLY - 1
Line 12
          FOR index FROM 0 TO LENGTH(values) - 1 DO
Line 13
             SET counter TO 0
Line 14
             IF values[index] >= 5.0 THEN
Line 15
                SET counter TO counter + 1
Line 16
             ELSE
Line 17
                IF counter > longestStreak THEN
Line 18
                   SET longestStreak TO counter
Line 19
                END IF
Line 20
                SET counter TO 0
Line 21
             END IF
Line 22
          END FOR
Line 23
          IF counter > longestStreak THEN
Line 24
                SET longestStreak TO counter
Line 25
          END IF
Line 26
          RETURN longestStreak
Line 27
        END FUNCTION
Line 46
        SET distances TO [5.2, 4.2, 4.0, 4.8, 5.8, 5.2, 6.4]
Line 47
        SET daysMet TO consecutiveDays(distances)
```



| 40  |           | 11 |
|-----|-----------|----|
| 10. | (continue | a) |

MARKS DO NOT WRITE IN THIS MARGIN

(a) Complete the trace table for the first two iterations of the loop.

The trace table should indicate the line number where a variable changes value and the new value of that variable.

3

| Line<br>number | counter | index | longestStreak |
|----------------|---------|-------|---------------|
| 10             | 0       |       |               |
| 11             |         |       | -1            |
| 12             |         | 0     |               |
| 13             | 0       |       |               |
| 15             |         |       |               |
| 12             |         |       |               |
| 13             |         |       |               |
| 18             |         |       |               |
| 20             |         |       |               |

| (b) | State the line number of the code that should be removed to correct the |
|-----|---|
|     | algorithm.  |

1

| (c) | Name and describe a debugging technique that could be used during |
|-----|---|
|     | execution of the code.  |

2

| (d) | Explain why the   | e scope of t | he variable  | counter i  | s loca |
|-----|-------------------|--------------|--------------|------------|--------|
| (u) | Explain willy the | 2 acope of t | ine variable | Counter 1. | 3 (0   |

1

| 4 | v | 0 | 1 | 4 | 7 | 4 | Ω | 1 | 1 | 5 | _ |
|---|---|---|---|---|---|---|---|---|---|---|---|

| MARKS | DO NOT         |
|-------|----------------|
|       | THIS<br>MARGIN |

2

| 40    | / <del></del> | راء ۔ . |
|-------|---------------|---------|
| 10. ( | (continu      | lea.    |

| ) | Describe how modular programming increases the efficiency and maintainability of the code. |
|---|--|
|   | Efficiency   |
|   |  |
|   |  |
|   |  |
|   | Maintainability  |
|   |  |
|   |  |

[END OF SECTION 1]